



US005865700A

**United States Patent [19]**  
**Horsch**

[11] **Patent Number:** **5,865,700**  
[45] **Date of Patent:** **Feb. 2, 1999**

[54] HYDRO-MECHANICAL TRANSMISSION

5,024,278	6/1991	Shuknecht .....	56/12.8 X
5,494,142	2/1996	Kale .	
5,505,267	4/1996	Orbach et al. .	
5,549,185	8/1996	Kale .	
5,667,452	9/1997	Coutant .....	475/80 X

[75] Inventor: Joachim Horsch, Lombard, Ill.

[73] Assignee: Case Corporation, Racine, Wis.

[21] Appl. No.: 847,195

[22] Filed: May 1, 1997

[51] Int. Cl.<sup>6</sup> ..... F16H 47/04

[52] U.S. Cl. ..... 475/72; 475/78; 475/82

[58] **Field of Search** ..... 475/72, 76, 78,  
475/80, 81, 82; 180/243, 307, 53.1; 56/12.8,  
10.1, 11.1, 10.8

[56] References Cited

## U.S. PATENT DOCUMENTS

3,396,607	8/1968	Ross .	
3,714,846	2/1973	Louis et al. ....	475/82 X
3,744,344	7/1973	Olsen et al. ....	475/82 X
3,796,111	3/1974	Schauer .....	475/82 X
3,903,756	9/1975	Hamma .....	475/82 X
4,019,404	4/1977	Schauer .....	475/82 X
4,138,907	2/1979	Melles .....	475/72 X
4,259,881	4/1981	Meyerle .....	475/72
4,348,855	9/1982	De Pauw et al. ....	56/10.2 X
4,471,668	9/1984	Elsner .....	475/72
4,487,002	12/1984	Kruse et al. ....	56/10.2
4,694,648	9/1987	Beck, Jr. .	
4,913,004	4/1990	Panoushek et al. .	

## FOREIGN PATENT DOCUMENTS

0 444 472 A2 2/1991 European Pat. Off. .  
4311 084 C1 4/1993 Germany .

*Primary Examiner*—Khol Q. Ta  
*Attorney, Agent, or Firm*—Foley & Lardner

[57]

A hydro-mechanical transmission for an agricultural work vehicle is provided including a motor, a clutch and a differential assembly. The clutch which is rotatably supported by a housing includes first and second input shafts and a first output shaft. The first output shaft is configured to selectively couple to the first and second input shafts. The motor is coupled to the second input shaft, and the differential assembly which is rotatably supported by the housing is coupled to the first output shaft. The differential assembly includes a third input shaft coupled to the first output shaft, and a fourth input shaft coupled to the motor, and a second output shaft. The speed of the second output shaft is a combination of the speeds of the third and fourth input shafts.

28 Claims, 3 Drawing Sheets

